

TTC Wärtsilä JOVYSTAR INDUSTRIE

PRODUCT LEAFLET



The assembly of all industrial UPS systems takes place in a customised way, entirely according to your requirements and requests. The installation of additional outputs or additional DC power supply as well as the type of cabinet, the colour, the position of further installations or more equipment features can be determined by the customer. As a matter of course comprehensive connection options to computer systems or to a central control station are available for these customised systems.

ONLINE UPS SYSTEM

As online systems (double converter, continuous transducers technology) TTC Wärtsilä JOVYSTAR INDUSTRIE UPS systems protect against system interferences and failures of any kind in a secure and economic way.

ROBUST UPS-TECHNOLOGY FOR INDUSTRIAL APPLICATION

The various requirements and application areas in the industry require specific designs of UPS systems and necessitate customer-specific adaptations or developments of UPS systems. Whether it is ambient conditions deviating from the norm, shock or vibration loads or the installation

of DC supply, patch panels or further additional installations: our engineers take into account your requests and requirements and create the respective professional and customised solution.

ASSEMBLY EASY TO SERVICE

All UPS systems of the TTC Wärtsilä JOVYSTAR INDUSTRIE series are installed easy to service, thus all main structural components are exchangeable with little effort. Depending on the application the batteries can be fitted into an UPS cabinet or mounted into a battery cabinet adapted to the design of the UPS system.

TYPES TTC Wärtsilä JOVYSTAR INDUSTRIE

	Dimensions W x H x D [mm]	Weight [kg]	Autonomy times [min]*
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/1-10	600 x 1970 x 800	235	0 - 13 - 35
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/1-15	600 x 1970 x 800	235	0 - 6 - 20 - 30
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/1-20	600 x 1970 x 800	245	0 - 5 - 13 - 20 - 35 - 60
Three Phases 3/3 10-150 kVA			
TTC Wärtsilä JOVYSTAR INDUSTRIE	600 x 1970 x 800	235	0 - 13 - 35
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-15	600 x 1970 x 800	235	0 - 6 - 20 - 30
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-20	600 x 1970 x 800	245	0 - 5 - 13 - 20 - 35 - 60
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-30	600 x 1970 x 800	320	0 - 10 - 20 - 30
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-40	600 x 1970 x 800	320	0 - 7 - 15 - 22 - 35
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-60	800 x 2170 x 800	688	0 - 5 - 10 - 15 - 30
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-80	800 x 2170 x 800	728	0 - 7 - 10 - 25 - 40
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-100	1200 x 2170 x 800	918	0 - 4 - 8 - 20 - 30
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-125	1200 x 2170 x 800	938	0 - 4 - 12 - 17 - 25
TTC Wärtsilä JOVYSTAR INDUSTRIE 3/3-150	1200 x 2170 x 800	1038	0 - 5 - 10 - 17 - 27

* further autonomy times on request

TECHNICAL DATA

	TTC Wärtsilä JOVYSTAR	TTC Wärtsilä JOVYSTAR
Power	10, 15, 20 kVA	10, 15, 20, 30, 40, 60, 90, 100, 125, 150 kVA
INPUT		
Voltage	3x400V/230V +15 % -20 % Bypass: 230 V	3x400V/230V + 15 % -20 %
Frequency	50 Hz / 60 Hz ± 5 Hz	
Efficiency	>0,99	
THD	<4 % (PFC)	
OUTPUT		
Voltage	1 x 230 V	3 x 380/220V / 3 x 400/230V / 3 x 415/240V
	±1% static load ±2% static, asymmetric load ±5% dynamic load (load step 0 % -->100 % --> 0 %)	
Frequency	50 Hz (60 Hz)	
Efficiency	cos phi = 0,8 inductive	cos phi =0,8 inductive
THD	THD-U = < 2% lin. load , THD-U = < 5% at crest factor 3:1	
Direct current link voltage	720 (2 x 360 V)	
Short time load	125 % for 10 min. 200 % for 100 ms, 1000 % for 1 period via bypass	
Crest Factor	3:1	
SETTING		
Protection Degree	IP 22	
Classification	VFI SS 111	
Temperature	UPS: 0°C up to +40°C battery: 0°C up to +25°C; optimal +20 °C	
Humidity	< 95 % (without condensation)	

COMMUNICATION

All system data can be accessed via an RS 232 / USB interface - optional they can be transmitted via RS 485, SNMP adapter, Modbus adapter, Profibus or via other bus systems

- **ONLINE UPS SYSTEM**
VFI /Double Converter Technology offers maximum safety for connected consumer loads
- **ROBUST INDUSTRIAL UPS**
in a solid industrial housing
- **COMFORTABLE OPERATION**
via menu-driven display and text output
- **RS 232 INTERFACE**
for monitoring of all system data
- **PERFORMANCE INCREASE**
via parallel connection of several systems feasible
- **STATIC BYPASS**
manually and automatically switchable

Fig.1 TTC Wärtsilä JOVYSTAR INDUSTRIE

